

---

# Upgraded version PRO 12V 5A car and motorcycle ship battery fully automatic compatible smart charger anti-overcharge CT E0061

product manual:

Model: CT E0061

Input voltage: AC 100~240V

Rated output: 13.8V~5A

Rechargeable battery specifications: 12~36V/ 10-60Ah

Charging method: Intelligent four-stage, full automatic shutdown

Charging status display: 4LED power indication 25%~100%

Output protection: anti-battery reverse connection protection, short circuit protection, over current, over voltage protection

Safety certification: CE

Dimensions: about 160\*95\*50mm

## Parameters:

Model: CT E0061

Input(v):100~200VAC

Power: 100W

Output(v): 4-15V

Output(A): 5A

Range: 15~120AH

Weight: 538.6g

Suitable: Lead-acid/Car Truck battery

Size: 145MM\*70MM\*50MM



---

Multiple configuration options:

1. 12V 5A Advanced configuration - black red shell version (16# red black line with high alligator clip and 8mm ring)
2. 12V 5A Standard configuration - black version (16# red black line with ordinary alligator clip and 8mm ring, black)
3. 12V 5A Standard configuration - red version (16# red black line with ordinary alligator clip and 8mm ring, red)
4. 12V 5A regular version - black version (black shell +18# side by side black line + ordinary alligator clip)
5. 12V 5A regular version - red version (red shell +18# side by side black line + ordinary alligator clip)

## **General types of DC output plug photos**



DCP-1 5.5\*2.1\*12mm



DCP-2 5.5\*2.5\*12mm



DCP-3 LOTUS



DCP-4 Anderson (SB30)

AC standard plugs worldwide (optional) (Asia, USA, Europe, Middle East, South Africa)?

American Standard



European standard



American Standard



European standard



British standard



Australian Standard



---

Product link : <https://www.gct-partszone.com/?p=2267>